



**New Built-In Model BI-36U  
Over-and-Under**

Over-and-under Model BI-36U offers large refrigerated storage, plus a convenient roll-out freezer drawer. Sub-Zero dual refrigeration along with new air purification and water filtration systems guard the freshness of your food and water like nothing before. Framed, overlay/flush inset and stainless steel models are available. New flush inset installation allows the unit to sit flush with surrounding cabinetry. Model BI-36U/S is Energy Star qualified.



*Model BI-36U shown with stainless steel flush inset panels and tubular handles.*

**Features**

- Framed, overlay/flush inset and stainless steel design applications
- Flush inset installation option allows unit to sit flush with surrounding cabinetry
- Air purification system
- Water filtration system
- Dual refrigeration system
- Model BI-36U/S is Energy Star qualified with \$49 annual energy usage
- Flip-up grille for easy access to condenser
- Evenly-distributed bright interior lighting
- Door shelves are adjustable in one-inch increments
- Crisper and deli drawers form a special low-temperature zone
- Informational freshness cards inside unit
- Max ice feature to increase rate of ice production for a 24-hour period

Model Options	BI-36U/F	BI-36U/O	BI-36U/S/TH	BI-36U/S/PH	BI-36U/S/CH
<b>Design</b>	Framed	Overlay/Flush Inset	Stainless	Stainless	Stainless
<b>Grille</b>	Louvered	Panel	Stainless	Stainless	Stainless
<b>Handle</b>	Full-Length	*	Tubular	Pro	Curved

*\*Handle not included to allow for design flexibility.*

**Interior Features**

- **Refrigerator**  
15.9 cu ft Capacity  
Air Purification System  
3 Adjustable Glass Shelves  
1 Stationary Glass Shelf  
1 High-Humidity Drawer with Dividers  
1 Storage Drawer with Dividers  
2 Adjustable Door Shelves  
Adjustable Dairy Compartment
- **Freezer**  
5.2 cu ft Capacity  
Water Filtration System  
Full-Extension Roll-Out Freezer Drawer  
Two-Tier Wire Storage Baskets  
Automatic Ice Maker

**Accessories**

- Louvered, panel and stainless steel grilles for 83", 84" and 88" finished heights
- Stainless steel front panels for framed, flush inset and dual flush inset applications with stainless steel finish and handle options
- Side panels in classic stainless steel and white
- Stainless steel tubular, pro or curved handles and full-length extended handles
- Dozen egg container with lid
- Dual installation kit
- 90° door stop kit



This appliance is certified by Star-K to meet strict religious regulations in conjunction with specific instructions found on [www.star-k.org](http://www.star-k.org).



Flip-Up Grille



Air Purification System




Accessories are available through your Sub-Zero dealer. To obtain local dealer information, visit the Showroom Locator section of our website, [subzero.com](http://subzero.com).



## Built-In Model BI-36U

### Overall Dimensions



### Specifications

Overall Dimensions	36"W x 84"H x 24"D
Door Clearance	Standard 37 1/4"
	Flush Inset 37 3/4"
Opening Width	35 1/2"
Flush Inset Width	38"
Opening Height	83 3/4"
Flush Inset Height	84"
Opening Depth	24"
Flush Inset Depth	26 3/16"
Electrical Requirements	115 V AC, 60 Hz 15 amp circuit
Plumbing Requirements	1/4" OD copper line 30–100 psi
Shipping Weight	482–515 lbs

### Installation Notes

Built-In models may be used in a standard installation or in a flush inset installation which allows the unit to be flush with surrounding cabinetry.

Built-In over-and-under models with opposite hinges can be used in a dual installation.


Complete installation specifications, including panel sizes, can be found on our website, [subzero.com](http://subzero.com).

### Installation Specifications

#### Standard Installation

\*Anti-tip bracket must not interfere with water line. Extend water line approximately 36" from back wall.

Dimensions in parentheses are in millimeters unless otherwise specified.



#### Flush Inset Installation

\*Anti-tip bracket must not interfere with water line. Extend water line approximately 36" from back wall.

\*\*Dimensions based on 3/4" (19) panels.

